

Northwest Florida Water Management District

Multi-Well Monitor Well Permits

For monitor wells to be eligible for a multi-well permit, all of the following conditions must be met:

- a. Be 4 inches or less in diameter
- b. Be 50 feet or less in total depth
- c. Be for monitoring purposes only
- d. Be constructed at a single project site for contamination assessment or cleanup (same section, township & range, owner and well address)

The pricing applies to construction, repair, or abandonment of the wells.

Fees: One flat fee of \$30.00 for up to “10” construction/repair wells and \$10.00 for up to “10” abandonment wells.

You will need to put “10” for the number of proposed wells in Section 7 of the application even if you aren’t doing ten wells. If wells are of different depths, put the deepest well depth on the permit application in Section 9.

Permits will receive only one permit number.

The multi-well permit is not available for aquifer restoration wells, sparge wells, bio-injection wells, or dual phase recovery wells. These types of wells are charged normal fees, not monitor well fees.

Completion reports must be submitted for each of the wells constructed, repaired, or abandoned under the multi-well permit. One completion report may be used for all the wells if all are constructed the same (diameter, total depth, cased depth, etc.) . The contractor must write on the completion report “**All wells are of similar total depth, cased depth, and diameter.**”

If the wells are different depths, put the deepest depth on the permit application and submit a separate completion report for each depth. Please also indicate on the completion report the number of wells drilled and the remaining wells to be cancelled.